



RA 12-75H (12V75Ah) (275.0w/cell)

RA12-75H is high rate series with 10 years floating design life, especially designed for high rate load discharge applications. By using strong grid and specific paste plate to insure high performance during big current discharge requirement when electricity is off., High Rate series offering extra-durable stable performance under high rate discharge.



Specification

Cells Per Unit	6
Voltage Per Unit	12
Capacity	275.0 W@15min-rate to 1.67V per cell @25°C
Weight	Approx. 24.8Kg
Max. Discharge Current	750 A (5 sec)
Internal Resistance	Approx. 4.5 mΩ
Operating Temperature Range	Discharge: -20°C~60°C Charge: 0°C~50°C Storage: -20°C~60°C
Normal Operating Temperature Range	25°C±5°C
Float charging Voltage	13.6 to 13.8 VDC/unit Average at 25°C
Recommended Maximum Charging Current Limit	22.5 A
Equalization and Cycle Service	14.6 to 14.8 VDC/unit Average at 25°C
Self Discharge	RITAR batteries can be stored for more than 6 months at 25°C. Self-discharge ratio less than 3% per month at 25°C. Please charge batteries before using.
Terminal	Terminal F11/F15
Constainer Material	A.B.S. (UL94-HB), Flammability resistance of UL94-V2 can be available upon request.



MH28539






G4M20206-0910-E-16



ISO9001:2000 Certificate

Dimensions

Unit: mm Dimension: 260(L)×169(W)×235(H)



Constant Current Discharge Characteristics : A(25 °C)


F.V/Time	2MIN	4MIN	6MIN	8MIN	10MIN	15MIN	20MIN	30MIN	60MIN	90MIN
9.60V	508.2	379.4	295.6	252.7	217.5	160.5	129.3	93.30	50.24	40.09
10.0V	473.7	354.7	276.0	239.4	205.7	153.5	121.8	89.85	48.38	38.70
10.2V	458.9	344.2	267.5	233.7	200.6	150.6	118.5	88.33	47.55	38.01
10.5V	435.0	326.3	258.7	224.9	190.8	145.4	116.7	86.94	47.41	37.53
10.8V	411.1	308.3	249.9	216.1	180.9	140.1	114.9	85.49	47.20	37.11
11.1V	387.2	290.4	241.1	207.3	171.2	134.9	113.1	84.11	46.93	36.63

Constant Power Discharge Characteristics : W(25 °C)


F.V/Time	2MIN	4MIN	6MIN	8MIN	10MIN	15MIN	20MIN	30MIN	60MIN	90MIN
9.60V	5469	4083	3181	2719	2336	1727	1413	1020	549.4	439.6
10.0V	5098	3818	2969	2576	2213	1653	1331	982.0	528.7	422.6
10.2V	4939	3704	2878	2515	2158	1621	1295	965.4	519.6	414.7
10.5V	4681	3511	2784	2420	2052	1564	1276	950.0	517.5	410.5
10.8V	4424	3317	2689	2325	1946	1507	1256	934.3	514.6	406.4
11.1V	4166	3124	2594	2231	1841	1451	1237	918.1	512.5	402.2

All mentioned values are average values.


Effect of temperature on long term float life




Storage characteristic



Charge characteristic Curve for standby use



Discharge characteristic Curve



Capacity Factors With Different Temperature

Battery Type		-20°C	-10°C	0°C	5°C	10°C	20°C	25°C	30°C	40°C	45°C
GEL Battery	6V&12V	50%	70%	83%	85%	90%	98%	100%	102%	104%	105%
	2V	60%	75%	85%	88%	92%	99%	100%	103%	105%	106%
AGM Battery	6V&12V	46%	66%	76%	83%	90%	98%	100%	103%	107%	109%
	2V	55%	70%	80%	85%	92%	99%	100%	104%	108%	110%

Discharge Current VS. Discharge Voltage

Final Discharge Voltage V/cell	1.75V	1.70V	1.60V
Discharge Current (A)	(A) ≤ 0.2C	0.2C < (A) < 1.0C	(A) ≥ 1.0C

Charge the batteries at least once every six months, if they are stored at 25°C.

Charging Method:

Constant Voltage	-0.2Cx2h + 2.4~2.5V/Cellx24h, Max. Current 0.3CA
Constant Current	-0.2Cx2h + 0.1CAx 12h
Fast	-0.2Cx2h + 0.3CAx4.0h

Maintenance & Cautions

Float Service:
※ Every month, recommend inspection every battery voltage.
※ Every three months, recommend equalization charge for one time.
Equalization charge method:
Discharge: 100% rate capacity discharge.
Charge: Max. current 0.3CA, constant voltage 2.4-2.45V/Cell charge 24h.
※ Effect of temperature on float charge voltage: -3mV/°C/Cell.
※ Length of service life will be directly affected by the number of discharge cycles, depth of discharge, ambient temperature and charging voltage.